

Declaration of Performance

No.: SYN-KLO-002-CE
Version: 03/2023

Permo Ultra 120
KU0041-1-15 / KU0041-1 / KU0041-1-11-15

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

Permo Ultra 120

2. INTENDED USE

Underlays for discontinuous roofing

3. MANUFACTURER

Klober GmbH
Scharpenberger Str. 72-90
58256 Ennepetal
Germany

4. AUTHORIZED REPRESENTATIVE

Klober Ltd
BMI House, 2 Pitfield, Kiln Farm, Milton Keynes MK11 3LW
United Kingdom

5. SYSTEM OR SYSTEMS AVCP

System 3

6. HARMONISED STANDARD or ETA

EN13859-1/-2: 2010

7. NOTIFIED BODY(IES)

DE - 0751 / 0761

Signed for and on behalf of the manufacturer by:

Markus Brando



Director Klöber GmbH
Germany
20.03.2023

8. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonized technical specification
Reaction to fire (EN13501-1)	F-Class	EN 13859-1/-2: 2010
Resistance to water penetration (EN1928)	W1	
Tensile strength (N/50mm) MD (EN 12311-1)	230 +/-30N/5cm	
Tensile strength (N/50mm) CD (EN12311-1)	160 +/-30N/5cm	
Elongation MD/CD (%) (EN12311-1)	100/120 (+/-10)	
Elongation after ageing MD/CD (%) (EN12311-1)	70/80 (+/-10)	
Resistance to tearing (N) (nail shank) MD (EN 12311-1)	140 +/-50N	
Resistance to tearing (N) (nail shank) CD (EN 12311-1)	180 +/-50N	
Pliability (EN1109)	-25°C	
Tensile strength after ageing (N/50mm) MD (EN12311-1)	210 +/-50N/5cm	
Tensile strength after ageing (N/50mm) CD (EN12311-1)	150 +/-50N/5cm	
Resistance to water penetration after ageing (EN1928)	W1	

NPD: No performance determined

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.